

# DMP 334

## Industrial Pressure Transmitter for High Pressure

Thinfilmm Sensor

accuracy according to IEC 60770:  
0.35 % FSO



### Nominal pressure

from 0 ... 600 bar up to 0 ... 2200 bar

### Analogue output

2-wire: 4 ... 20 mA  
3-wire: 0 ... 10 V  
others on request

### Special characteristics

- ▶ extremely robust and excellent long-term stability
- ▶ pressure sensor welded

### Optional versions

- ▶ IS-version  
Ex ia = intrinsically safe for gases and dusts
- ▶ pressure port: M20 x 1.5 or 9/16 UNF
- ▶ adjustability of span and offset
- ▶ different kinds of electrical connections

The industrial pressure transmitter DMP 334 has been especially designed for use in hydraulic systems up to 2200 bar. The base element of DMP 334 is a thinfilm sensor, that is welded with the pressure port and meets high demands of accuracy and reliability.

All of the characteristics and the excellent measurement data of DMP 334 as well as distinguished offset stability offer a pressure transmitter with easy handling, reliability and robustness for hydraulic user. The DMP 334 is deliverable with standard HP connections.

### Preferred areas of use are



Plant and Machine Engineering



Commercial Vehicles and Mobile Hydraulics



# DMP 334

Industrial Pressure Transmitter

Technical Data

Input pressure range						
Nominal pressure gauge	[bar]	600 <sup>1</sup>	1000	1600	2000	2200
Overpressure	[bar]	800	1400	2200	2800	2800
Burst pressure ≥	[bar]	3000	4000	6000	6000	6000
<sup>1</sup> only available with pressure port G 1/2" EN 837						
Output signal / Supply						
Standard	2-wire:	4 ... 20 mA / V <sub>S</sub> = 12 ... 36 V <sub>DC</sub>				
Option IS-protection	2-wire:	4 ... 20 mA / V <sub>S</sub> = 14 ... 28 V <sub>DC</sub>				
Option 3-wire	3-wire:	0 ... 10 V / V <sub>S</sub> = 14 ... 30 V <sub>DC</sub>				
Performance						
Accuracy	≤ ± 0.35 % FSO IEC 60770 <sup>2</sup>					
Permissible load	current 2-wire:	R <sub>max</sub> = [(V <sub>S</sub> - V <sub>S</sub> min) / 0.02 A] Ω				
	voltage 3-wire:	R <sub>min</sub> = 10 kΩ				
Influence effects	supply:	0.05 % FSO / 10 V			load: 0.05 % FSO / kΩ	
Long term stability	≤ ± 0.2 % FSO / year at reference conditions					
Response time	< 5 msec					
Adjustability	Adjustment of offset is possible within the range of ± 5 % of the nominal pressure range, without an influence of characteristic curve and accuracy.					
<sup>2</sup> accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)						
Thermal effects (Offset and Span) / Permissible temperatures						
Thermal error	≤ ± 0.25 % FSO / 10 K in compensated range -20 ... 85 °C					
Permissible temperatures	medium:	-40 ... 140 °C		electronics / environment:	-25 ... 85 °C storage: -40 ... 100 °C	
Electrical protection						
Short-circuit protection	permanent					
Reverse polarity protection	no damage, but also no function					
Electromagnetic compatibility	emission and immunity according to EN 61326					
Mechanical stability						
Vibration	10 g RMS (20 ... 2000 Hz)					
Shock	100 g / 11 msec.					
Materials						
Pressure port	stainless steel 1.4542 (17-4 PH)					
Housing	standard:	stainless steel 1.4404 (316L)				
	field housing:	stainless steel 1.4404 (316L), cable gland: brass, nickel plated				
Seals (media wetted)	none (welded version)					
Diaphragm	stainless steel 1.4542 (17-4 PH)					
Media wetted parts	pressure port / diaphragm					
Explosion protection (only for 4 ... 20 mA / 2-wire)						
Approvals DX19-DMP 334	<b>IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X</b> zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T 85°C Da					
Safety technical maximum values	U <sub>i</sub> = 28 V <sub>DC</sub> , I <sub>i</sub> = 93 mA, P <sub>i</sub> = 660 mW, C <sub>i</sub> ≈ 0 nF, L <sub>i</sub> ≈ 0 μH, the supply connections have an inner capacity of max. 27 nF to the housing					
Permissible temperatures for environment	in zone 0:	-20 ... 60 °C with p <sub>atm</sub> 0.8 bar up to 1.1 bar				
	in zone 1 or higher:	-20 ... 70 °C				
Connecting cables (by factory)	cable capacitance:	signal line/shield also signal line/signal line: 160 pF/m				
	cable inductance:	signal line/shield also signal line/signal line: 1 μH/m				
Miscellaneous						
Current consumption	signal output current:	max. 25 mA				
	signal output voltage:	max. 8,5 mA				
Weight	approx. 240 g					
Installation position	any					
CE-conformity	EMV-Richtlinie: 2014/30/EU			Druckgeräterichtlinie: 2014/68/EU (Modul A)		
ATEX-Richtlinie	2014/34/EU					
Wiring diagrams						
2-wire-system (current)			3-wire-system (current / voltage)			

# DMP 334

Industrial Pressure Transmitter

Technical Data

Pin configuration					
Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1 (4-pin)	Field housing	Cable colours (IEC 60757)
Supply +	1	3	1	IN +	wh (white)
Supply -	2	4	2	IN -	bn (brown)
Signal + (only for 3-wire)	3	1	3	OUT+	gn (green)
Shield	ground pin	5	4		gnye (green-yellow)

  

Electrical connections (dimensions in mm)					
<b>standard</b>	<b>option</b>	<b>M12x1</b>	<b>cable outlet</b>	<b>compact field housing</b>	
ISO 4400 (IP 65)	Binder series 723 (IP 67)	M12x1 4-pin (IP 67)	cable outlet (IP 67) <sup>3</sup> with PVC cable	compact field housing (IP 67)	

<sup>3</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)

  

Mechanical connection (dimensions in mm)		
<b>standard</b> <sup>4</sup>	<b>option</b> <sup>4</sup>	
ISO 4400	ISO 4400	ISO 4400
33	33	33
60,5	110	70,5
Ø 26,5	Ø 33,5	Ø 33,5
SW 27	SW 30	SW 27
23	77	11
3	15	
G1/2"	12,5	Ø 30
G1/2" EN 837 <sup>5</sup>	M20x1,5	9/16-18 UNF
	Ø 35	
	M20x1.5 internal thread	9/16-18 UNF internal thread

<sup>4</sup> adjustable version is not possible in combination with IS-version, compact field housing and cable outlet  
<sup>5</sup> According to EN 837, the pressure port and the complement at pressure over 1000 bar must be preferably made of stainless steel with a tensile strength of  $R_p > 260 \text{ N/mm}^2$  in accordance with DIN 17440. The maximum allowed pressure is 1600 bar!

© 2016 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

## Ordering code DMP 334

DMP 334



<b>Pressure</b>																												
	gauge	1	4	0																								
<b>Input</b>		[bar]																										
	600	1			6	0	0	3																				
	1000				1	0	0	4																				
	1600				1	6	0	4																				
	2000				2	0	0	4																				
	2200				2	2	0	4																				
	customer				9	9	9	9																				consult
<b>Output</b>																												
	4 ... 20 mA / 2-wire								1																			
	0 ... 10 V / 3-wire								3																			
	Intrinsic safety 4 ... 20 mA / 2-wire								E																			
	customer								9																			consult
<b>Accuracy</b>																												
	0.35 %								3																			
	customer								9																			consult
<b>Electrical connection</b>																												
	Male and female plug ISO 4400								1	0	0																	
	Male plug Binder series 723 (5-pin)								2	0	0																	
	Cable outlet with PVC cable								T	A	0																	
	Male plug M12x1 (4-pin) / metal								M	1	0																	
	Compact field housing								8	5	0																	
	stainless steel 1.4404 (316L)																											
	customer								9	9	9																	consult
<b>Mechanical connection</b>																												
	G1/2" EN 837											2	0	0														
	M20x1.5 internal thread											D	2	8														
	9/16 UNF internal thread											V	0	0														
	customer											9	9	9														consult
<b>Seals</b>																												
	without (welded version)																											
	customer																											consult
<b>Special version</b>																												
	standard (adjustable)																											
	IS version, cable outlet, field housing																											
	customer																											consult

<sup>1</sup> only available with pressure port G1/2" EN 837

<sup>2</sup> different cable types and lengths deliverable

<sup>3</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C), optionally cable with ventilation tube

<sup>4</sup> According to EN 837, the pressure port and the complement, at pressure over 1000 bar must be preferably made of stainless steel with a tensile strength of  $R_p > 260 \text{ N/mm}^2$  in accordance with DIN 17440. The maximum allowed pressure is 1600 bar!

<sup>5</sup> not possible in combination with IS-version, compact field housing and cable outlet with PVC cable