



ADOS
e s t . 1 9 0 0

Instrumentation and Control



MULTI-CHANNEL GAS WARNING SYSTEM

MWVS 903



ADOS GmbH

Tel: +49 (0) 2 41 / 97 69 - 0

Instrumentation and Control

Fax: +49 (0) 2 41 / 97 69 - 16

P.O. Box 500 444 · 52088 Aachen · FRG

info@ados.de

Trierer Strasse 23-25 · 52078 Aachen · FRG

www.ados.de

since 1997
DIN EN ISO 9001
ID: 0110071011



Application

The **multi-channel gas warning equipment MWS 903** continuously monitors the surrounding air and provides an early warning of dangerous, explosive and non-combustible gases and vapours. Possibility to connect up to 8 gas transmitters to the unit.

Fields of Application

Monitoring of:

- Heating systems
- Garages
- Liquid gas storage rooms
- Laboratories
- Cold-storage houses
- Plastic processing plants
- Chemical industries
- Paint manufacturing plants
- Concentration measurement of O₂
- and many more

Features

- 6-section keyboard and illuminated 4-line LC-Display for indicating actual values, half-hourly average values and fault messages, all clear text encoded
- Ready, Fault and Gas warning display
- Menu-assisted settings for the equipment parameters, via 6-section keyboard
- Two alarm thresholds for each sensor, independently adjustable from 5 to 100% of the measurement range; facility for forming half-hourly average value
- A maximum of 12 floating alarm outputs for controlling extra warning and control devices
- Floating change-over contacts for fault, siren and warning banners
- Serial interface output RS 232 for connecting a printer or PC
- 4 – 20 mA current interface
- Plastic, wall-mounted housing
- High operational reliability
- Low current consumption
- Easy installation
- USP unit available

Example of measurable gases

Gas	Formula
Acetylene	C ₂ H ₂
Alcohol	e.g. C ₂ H ₆ O
Ammonia	NH ₃
Butane	C ₄ H ₁₀
Carbon dioxide	CO ₂
Carbon monoxide	CO
Carbon tetrachloride	CCl ₄

Chloroform	CHCl ₃
Ether	C ₄ H ₁₀ O
Helium	He
Hydrogen	H ₂
Hydrogen chloride	HCl
Methane (natural gas)	CH ₄
Neon	Ne
Oxygen	O ₂
Petroleum spirit	
Propane	C ₃ H ₈
Toluene	C ₇ H ₈
Xylene	C ₈ H ₁₀

Accessories

Signal horn (siren), warning light, warning banner, test meters, plotter, stand-by power supply UPS 2000 24 V. Additional accessories will be offered, according to the system required. An early warning of dangerous, explosive and non-combustible gases and vapours.

Technical Data

Sensor inputs:	8 two- or three-wire sensors (e.g. LCTR 903) with current interface, 4 – 20 mA
Sensor supply:	24 V= / 200 mA
Ranges:	CO 0–300 ppm NO ₂ 0–30 ppm CH ₄ 0–100 % LEL CO ₂ 0–10 Vol % other ranges on request
Ambient temperature:	-10 °C to +40 °C
Digital inputs:	1 input for siren cancel
Digital outputs:	max. 12 alarms 1 fault relay 1 siren relay 1 warning banner relay All outputs have floating change-over contacts, max. rating 250 V/4 A
Standard output signals:	Analog output 4 – 20 mA serial interface RS 232
Mains connection:	230 V / 50 Hz 115 V / 60 Hz (optional) 24 V= (optional)
Dimensions (WxHxD):	240 x 160 x 90 mm
Weight:	approx. 2 kg
Protection:	IP 54, to DIN 40050